
Task K/HF: CMS PHYSICS AT BU...

FOCUSING ON QUARTZ CHERENKOV FORWARD CALORIMETRY

with Fermilab, Iowa (Y. Onel), and Texas Tech (N. Akchurin)



M. Oriunno, Engineering Design Review, 31 Jan 2006

Faculty L. Sulak, with J. Rohlf

Students: M. Carleton, C. Hugon*, and N. Sen*

Electronic Engineers, EDF: E. Hazen and S. Wu

Engineering Faculty: J. Sullivan (Aerospace and Mechanical) + senior student design team

Mechanical Engineer, SIF: D. Osborne

...those who are here today

^{*}Candidate PhD students, trained by LRS at Marseille during 2 year DOE sabbatical; pending DOE support

Forward Calorimeter: In this presentation



Why Cherenkov, sensitive only to π^{o} component of jet?

to record jets to η ~5, need optical sensitivity out to η ~ 5.5 due to e-shower radius but 100% occupancy beyond η ~4 at design luminosity only technology possessing full baseline restoration within 25 ns bunch spacing

Why Quartz?

only material transparent up to Grad and high neutron fluence, i.e. ~ 5 years @ 10^{34} quartz-clad quartz (silica) fibers lose 30% of light beyond $\eta \sim 4$ but plastic-clad quartz installed...choice driven by cost... $\sim 90\%$ loss after ~ 5 years

In this update for HF?

Current state of HF and BU contributions


How we helped get us here

What performance is expected? after extensive beam evaluations:

BNL, FNAL, CERN

HF CERN test beam calibration summer '05 simulation tuned by beam tests as luminosity monitor

Proposed BU work over next 3 years




100 GeV pion showers into central tower of 7 BU/HF modules in CERN test beam 1999





fast, rad hard quartz fiber technology won over European gas PPCs in CMS $3 < \eta < 5$ HF provides full coverage for forward jets, $\sim 1/2$ of phase space




11



$H \rightarrow Z Z \rightarrow \ell \ell j j$ in HF?

two forward jets critical to identifying high mass Higgs production by vector boson fusion

$$p_t > 10 \text{ GeV/c}$$




low level of background ⇒ benefit greatly from high luminosity of Super-LHC even if Higgs has low mass, important to measure WW, WZ, and ZZ coupling at high energy

DOE Site Visit - CMS Task

November 8, 2006, L. Sulak



the HCal End cap to Forward Calorimeter transition... overlap at $\eta = 3$ a big challenge for jet reconstruction




(physically HF is "small," 1.9 m along beam line, 1.4 m in radius)

M. Oriunno, Engineering Design Review, 31 Jan 2006



Cross section of HF along beam line through center of wedge (1 of 18 from each of two HFs) jets from the interaction region (IR) enter from the right, going left



full length fibers starting at front sample electromagnetic component short fibers starting at vertical red line sample hadronic content

light from left end of fibers guided to pms in readout boxes at upper left

M. Oriunno, Engineering Design Review, 31 Jan 2006



several HF wedges after hand-stuffing of quartz fibers, September 2005...



not shown: a light mixer, air light guide*, then phototube mount on each circular fiber bundle, allowing easy maintenance

* developed by D. Osborne, BU

CERN oreach photo 2005-012

assembled HF minus, July 2006 under test with radioactive source calibration, Task K/HF doing its share at CERN Meyrin before move from assembly area to intersection region





collision end lead shielding doors open, concrete plug neutron absorbers visible

300 ton HF + "on the move" last week

rolling on 182 wheels



just before a "soft landing"



PM boxes must be recabled to BU front ends, and cable track installed confirm operation with LEDs at PMs and with lasers pulses to ends of towers check with wire sources calibration of this summer


(Feb '07)

we from Task K/HF will be there, as we were this summer BU Mission: insure integrity of data, at each step until high luminosity (3 years)

BU Photo, Matt Carleton








must replace damaged plastic clad fiber in central region after ~ 5 years

from Task K renewal for 2000

How well should it work? particle identification capability?

2 typical simulated showers





code for optimizing design and modeling results from test beam studies next job for Task K/HF: add HF to Physics TDR, *e.g.*

 $H \rightarrow Z^{o}Z^{o} \rightarrow e^{+}e^{-}$ e⁺e⁻ from vector boson fusion: HF not yet studied


time to incorporate HF into FNAL LHC Physics Center (LPC) working with Daniel Elvira, using summer '05 test beam data

Akchurin, http://hepd.pnpi.spb.ru/~rdms2005



Resolutions critical to jet energy and missing E_t ?

HF lowest curves (open circles, labeled $3.0 < \eta < 5.0$) HCal End Cap middle curves HCal Barrel top curves




HF has the best resolution of the 3 elements of HCAL


All details in

"Design, Performance and Calibration of CMS Forward Calorimeter," G. Baiatian *et al.* N. Akchurin, primary author, LRS, editor, submitted to NIM this fall


Acosta, Physics TDR 1, CERN/LHCC 2006-001







writing, maintaining the test beam documentation, and taking test beam shifts...



software by M. Carleton, BU

proposed Task/HF work at BU over next 3 years?



HF must be fully operational at LHC startup next Sept 1

HF is CMS luminosity monitor, with web readout directly to control room the "Boston, Maryland, Princeton Project"

HF shakedown...before close on Sept 1...only 9 more months...can't wait

on-detector front end electronics reinstallation and commissioned

LED at each PM

lasers light to end of each tower

recalibration of each tower with radioactive source wire driver (firing on cosmic ray showers?)

tuning HF timing for 100% occupancy, after stable beam, 2008

phase each tower for in-time signal at beginning of 25 ns digitization period any signal over two periods = out-of-time, beam-related background

data quality monitoring

insure integrity of critical physics observables:

jet energy, jet direction, electron/hadron shower ID

need grad student on CMSSW analysis package...now

plastic/quartz degradation and annealing with exposure and time since beam complex calibration issue...LRS working with Merlo & Mayda Velasco



HF for the Super-LHC shutdown 2012: HF electronics upgrade to avoid event ambiguity?

upgrade for SLHC: 12.5ns or 75ns projected repetition times*

12.5ns: HF would need new front-end

Hazen, and LRS, considering HF options

(ok for HB & HE: long scintillator decay time spreads pulse over cycles)

* Jordan Nash, http://cmsdoc.cern.ch/cms/electronics/html/elec_web/docs/slhcusg/JN_CMS_Perspective.ppt

Evaluation of replacement of inner quarts fibers: plastic-clad to quartz-clad

in event of catastrophic beam loss

(remember UA 1 scintillator)

for 10 times more luminosity at Super LHC, before HF is too hot due to LHC

2007: Assessment of space and mounting

2008: R&D for automatic fiber stuffer

2009: Upgrade plan for fiber recycling for Super-LHC, shutdown of 2012



details of proposed study for replacing plastic-clad with quartz-clad fibers for high η?

Mechanical & chemical radiation damage of plastic-clad quartz fiber

characterize for neutrons at MIT research reactor do fibers still slide, does plastic coating become sticky in radiogenic O₃ or NO₂ corrosive atmosphere function of fluence, flux exposure

using same steel grooves, humidity, etc.
measure change of surface and bulk properties
complement work in proton and electron beams by Merlo at LIL/CERN
changes in transverse dimensions of steel laminates, grooves size change?

e.g. destroying hole registration?

Auto-replacement of quartz fibers

prepare and design prototype an automated fiber stuffer for the super-LHC

(Sullivan + senior design team from Engineering)

(Osborne)

(with Matt Carleton)

Before HF too "hot" to approach, at CERN

verify fixations & space at back of HF; are we ready to support an auto stuffer?

Confirming hole positions after darkened fibers withdrawn:

diffusion welded steel plates, using a gas first, then a wire?

Vetting double, 2D pinch roller design for stuffing fibers

feed fibers one-by-one, achievable with only 90 degree access?

pneumatic tube feeding of fibers? servomotor or stepping motor control? classic "control theory" problems

specialties of our Aerospace and our Manufacturing Eng. Dep'ts

time budget for replacement, e.g. radio activation of the steel.

how long a shut down necessary for radiation levels to drop?

(robotic and NASA satellite work)





Shakedown and commissioning of HF, *in situ*,

LED, laser, and radiation source monitoring, cosmic showers

Recalibrate with wire sources

with collaborators...

"we never have enough help on HF," Aldo Penzo, CERN HF manager

Run as luminosity monitor for beam optimization, and for data at low luminosity

Tune phase of each tower on low intensity beam so that true pulses fully in bucket

During beam shutdown, valuate potential inner fiber replacement

Final conceptual engineering of fiber replacement

Tune with high intensity beam

we're eager to continue to do realize the potential of HF excited about the physics it will make possible



RESERVE

Probable timeline for HF operations over the 3 years of this renewal proposal

(BU/HF personnel at CERN) (Carleton, Sulak)

June - July '06 finished initial check out of both HFs at assembly hall

July '06 both HFs moved from CERN Assembly Building 186 at Meyrin to surface building at SX5

Aug '06 lower each HFs down to center of pit, then to garage positions at either end

Aug - Sept '06 HCAL Test Beam '06:

(Carleton, Sulak)

Confirm that production grade electronics operates as anticipated in an accelerator environment prone to ground loops, RF pickup, correlated noise, *etc*.

October '06 Install and connect moveable cable chains to HF

lay cables; connect to counting house, continuity test of cables

> Nov '06 limited tests of HFs in the pit potentially possible

Jan-Feb '07 confirm that both HFs survived the move to the pit and are fully operational

(Hugon, Sulak)

Cross check all channels of both HFs with onboard LEDs

test entire chain with laser in counting house

Calibrate HF+ to 5% with radioactive source and high statistics in garage

May '07 move HFs out of their garages, raise 15 m up to beam height, open them

June '07 before HFs get activated, plan mounting of fixtures for emergency fiber replacement and

for Super LHC

(Osborne, Sulak, Sullivan)

June-Aug '07 calibrate HF- to 5%

Recheck calibrations of HF+ in final position at beam height

cross check all channels

commission and shake down electronics in counting house

Trigger on cosmic rays

final tests before beam closure

(Carleton, Hugon, Sen, Sulak)

September '07 accelerator ring closes for initial engineering run

HF commissioning as luminosity monitor

Monitor HF fibers for rad damage; measure and characterize attenuation changes

"beam commissioning to injection energy, E_{cm} = 0.9 TeV and engineering run" at low luminosity with few

bunches

Increase luminosity, bunch number, and energy in planned phases [3,7]

Dec'07 - Mar '08 annual 3 month beam shutdown

Maintenance work on HF:

Replace pms, electronics, etc. that have succumbed to infant mortality

recalibrate both HFs with sources to track rad damage

March - Dec '08 first physics run at 10% design luminosity

June '08 data taking (Sulak)

Summer '08 (Carleton, Hugon, Sen)

Winter '09 annual 3 month beam shutdown

HF maintenance after first significant running (Sulak)

replace pms, electronics, etc.

Final work to plan automatic fiber replacement (Osborne, Sulak, Sullivan)


March – Dec '09 second year of physics running, full design luminosity

Summer '09 data taking (Carleton, Hugon Sen)

August '09 (Sulak)


Winter '10 annual 3 month beam shutdown, HF Maintenance (Hugon, Sulak)














rapidity distribution of tagging jets produced in heavy Higgs production



 $3 < \eta < 5$ range of HF provides full coverage for forward jets, $\sim 1/2$ of phase space

Kunori; Gavrilov, http://hepd.pnpi.spb.ru/~rdms2005/



absorber wedge during hand-stuffing of quartz fibers



bundles at high rapidity, high radiation region (top of wedge) last to be stuffed, easiest to remove

CERN oreach photo 2005-012

300 ton HF + "on the move" last week just below ground level







